



Portable Sound

D.A.R.T. DIGITAL ACTIVE REINFORCEMENT TOOL

Active 310W F.O.H. or Monitor..... \$2350.00

- Delivers strong and clear monitor sound without the hassle of endless tweaking and tuning
- 12" speaker for punchy low mids and excellent speech intelligibility
- 1" driver with 60° x 40° CD horn for transparent mid-range and crisp top end
- Digital power amp with 250 watts RMS and over 90% efficiency for powerful lows and low mids
- Power amp with 60 watts RMS for the 1" driver
- Two-way active circuitry featuring OFRTM technology reproduces the full spectrum of sound at any level
- MultiBand limiting for key frequency ranges
- Multi-functional design with DuoTilt™ speaker stand mounting collar
- Balanced, separately adjustable microphone and line inputs
- RCA connector for patching in signals from CD or tape
- Tricolor LEDs for displaying limiter status
- Included two-band EQ makes sound-shaping fast and easy



AVAILABLE D.A.R.T. ACCESSORIES

- DART-CS Protective Cover \$75

F.A.S.T. FLEXIBLE ACTIVE SOUND TOOL

Active 300W Multifunction spk cab..... \$1650.00

- 300 W power amp
- 12" Low/Mid speaker
- 1" CD horn 60°x 40°
- XLR microphone input
- Combination XLR - 1/4" jack line input
- DynaClip™ Limiter
- OFR™ technology
- Subsonic Filter
- DuoTilt™ speaker stand mounting collar (lines up sound to project toward the audience)
- Multifunctional housing



AVAILABLE F.A.S.T. ACCESSORIES

- FAST-CS Protective Cover \$75

PREMIUM PR:O

PREMIUM PR:O PASSIVE SPEAKER SYSTEMS

1" driver • high maximum SPL (128 dB) • ergonomically formed handles • comes standard with flypoints • integral hi/low-pass crossover in the bass unit • DuoTilt™ speaker-stand mounting cup • M20 pole-mount cup in the bass cabinet • Speakon® connectors • recessed connector panels for plug protection • casters available as an option

PRO-12

PRO-12M

PRO-15

PRO-18S

PRO-15X



	PRO-12	PRO-12M	PRO-15	PRO-18S	PRO-15X
R R P	\$995.00	\$975.00	\$1095.00	\$1450.00	\$1175.00
Power Handling capacity nominal	400W RMS	400 W RMS	400 W RMS	500 W RMS	400W RMS
Power Handling program	800 W	800 W	800 W	1000 W	800 W
Frequency response - 10dB 3)	60Hz - 19kHz	63Hz - 19kHz	53Hz - 19kHz	38Hz - 150Hz	53Hz - 19kHz
Sensitivity 1W@1m 1	104dB	104dB	104db	104db	104db
Maximum SPL 10% THD half-space	128 dB	128 dB	128 dB	129 dB	128 dB
Impedance	8 Ohms	8 Ohms	8 Ohms	4 Ohms	8 Ohms
Crossover Frequency	2 kHz/12 db Octave	2 kHz/12 db Octave	2 kHz/12 db Octave	150 Hz/12 db Octave	2 kHz/12 db Octave
Connectors	2x Speakon	2x Speakon	2x Speakon	2x Speakon	2x Speakon
Mounting collar	DuoTilt™ speaker-stand mounting collar for fast, easy orientation of the speakers towards the audience	-	DuoTilt™ speaker-stand mounting collar for fast, easy orientation of the speakers towards the audience	DuoTilt™ speaker-stand mounting collar for fast, easy orientation of the speakers towards the audience	DuoTilt™ speaker-stand mounting collar for fast, easy orientation of the speakers towards the audience
Rigging points	side-mounted M8 threaded rigging points for easy installation	-	side-mounted M8 threaded rigging points for easy installation	side-mounted M8 threaded rigging points for easy installation	-
Weight	18.2 kg	16 kg	21.1 kg	41.6 kg	21.6 kg
Dimensions (w x h x d) cm	39 cm x 57 cm x 36 cm	39 cm x 55,5 cm x 38 cm	47 cm x 61,5 cm x 41 cm	53 cm x 61 cm x 64 cm	47 cm x 61,5 cm x 44,5 cm

